



OLED Broadcast Monitors Support Critical Color Evaluation

September 25, 2026

LAKE FOREST, CA - September 25, 2026 -

Maintaining precise visual reference standards across modern television and motion picture production has become increasingly critical as high-luminance HDR workflows expand throughout the media industry. To support colorists, digital imaging technicians, and broadcast engineers navigating these technical demands, Boland Communications developed the X4K-OLED HDR Series to address color shift and black-level instability common in traditional liquid crystal reference panels. Utilizing self-emissive panel technology alongside Quantum Dot color layer integration, the series provides critical color grading environments with high-contrast picture reproduction and wide viewing angles across varying studio lighting conditions. Incorporating OLED broadcast monitors into live production control rooms and post-production suites allows technical teams to evaluate shadow details, peak highlight levels, and wide color gamuts under rigorous industry standards without relying on backlight-assisted display panels. Early deployment enables engineering staff to establish consistent visual benchmarks across multi-camera studio setups, master control facilities, and mobile location trucks.

Managing uncompressed 4K and Ultra High Definition video signals requires monitoring architecture capable of processing high-bandwidth data streams without introducing signal attenuation or frame latency.

Traditional edge-lit and direct-lit liquid crystal displays often exhibit light bleed, clouding, and halo artifacts around bright objects set against dark backgrounds. Self-emissive OLED panel structures eliminate these backlight artifacts by allowing each individual pixel to generate its own light or turn off completely, yielding exceptionally high contrast ratios and true black reproduction. Under Society of Motion Picture and Television Engineers ST 2082 specifications for 12G-SDI single-link transport, high-resolution video signals travel directly to internal 10-bit color processing engines, simplifying cable routing infrastructure and reducing patch panel complexity within mobile broadcast vehicles and studio control rooms.

Evaluating HDR content requires strict adherence to established electro-optical transfer functions and expanded color space specifications. According to technical recommendations published by the International Telecommunication Union, modern broadcast standards require display systems to cover wide color gamuts beyond traditional Rec. 709 parameters, extending into DCI-P3 and BT.2020 color spaces. The hardware architecture within OLED broadcast monitors supports Perceptual Quantization under SMPTE ST 2084, Hybrid Log-Gamma under BT.2100, and S-Log3 camera curves, along with user-definable 10-bit 3D Look-Up Table imports via USB interfaces. Built-in diagnostic tools, including dual-waveform monitors, vectorscopes, peaking focus filters, and false-color exposure indicators, enable technical directors, colorists, and camera operators to verify luminance levels and exposure margins objectively during live multi-camera production.

As broadcast facilities transition from traditional baseband matrix routing toward IP-based network infrastructures, reference monitoring systems must integrate directly into software-defined broadcast environments. Incorporating optional SMPTE ST 2110 IP connectivity with NMOS discovery protocols enables display units to receive uncompressed digital video over managed network switches, supporting decentralized control rooms and remote production workflows. The display lineup from Boland Communications encompasses screen sizes ranging from compact field units for on-set monitoring to large-format studio displays for client viewing rooms, accommodating varied operational requirements. While self-emissive display technology enhances visual reference consistency, achieving optimal color reproduction depends on proper ambient lighting control, routine display calibration, and standardized signal distribution throughout the media production pipeline.

Boland Communications is a commercial manufacturer of professional video monitors headquartered in Lake Forest, California. Operating for more than four decades, Boland Communications engineers specialized display solutions for broadcast television, motion picture production, commercial aviation, medical facilities, and government installations worldwide. Boland Communications provides custom hardware engineering, multi-format signal compatibility, and rugged enclosure designs built for demanding industrial applications. For more information, visit bolandcom.com/series/x4k-oled-hdr-series/.

###

For more information about Boland, contact the company here: Boland Boland (800) 918-9090 boland@gmail.com 16 Rancho Circle Lake Forest, California 92630

Boland

Website: [https://www.bolandcom.com/https://](https://www.bolandcom.com/)

Email: boland@gmail.com

Phone: (800) 918-9090

