Alamo Glass Expands Mirror Fabrication Capacity and Consultation Services

October 06, 2026

AUSTIN, TX - October 06, 2026 -
Responding to sustained regional commercial development and residential renovation activity across Central Texas, Alamo Glass has completed a $250,000 capital expansion of its site-consultation operations and fabrication of custom mirrors in Austin. Commissioned in October 2026, the operational investment adds high-precision automated cutting tables, automated edge-beveling lines, and specialized laminating machinery at its North Lamar Boulevard plant. The upgrades increase the company?s daily mirror processing throughput from 500 square feet to 1,200 square feet, doubling its capacity to serve commercial general contractors, interior design firms, and property managers.

The operational expansion addresses documented construction growth across the Austin metropolitan area. Modern architectural design plans in Travis County increasingly incorporate large-format reflective surfaces to maximize natural daylighting and improve indoor spatial efficiency. In high-density residential environments, such as urban mid-rises in Downtown Austin and historic home restorations in Hyde Park, interior light penetration is frequently restricted by adjacent structural footprints. Strategically placed wall mirror installations bounce ambient sunlight into interior hallways and living spaces, creating perceived visual room depth.

Commercial interiors account for a substantial portion of the increased regional fabrication volume. Commercial fitness centers, dance studios, medical offices, and retail storefronts require large-format mirror arrays built to strict physical safety criteria. Under architectural building codes and American National Standards Institute (ANSI) Z97.1 specifications for safety glazing materials, glass installed in hazardous or high-impact locations must meet defined impact resistance standards. While standard silvered float glass is not an inherently rated safety glazing material on its own, applying an adhesive-backed polyolefin safety film to the rear surface allows standard mirror sheet stock to pass ANSI Z97.1 impact testing. This safety backing retains glass fragments upon breakage, helping prevent scatter injuries in high-traffic public spaces. Alamo Glass has integrated dedicated roll-laminating equipment to streamline production of these safety-backed assemblies alongside specialty fabrications, such as two-way observation mirrors and custom geometric display cuts.

The company?s expanded site-consultation services provide preliminary technical evaluations prior to shop fabrication. Technical guidelines published by the National Glass Association (NGA) in technical paper FB21-09 (Installation Techniques Designed to Prolong the Life of Flat Glass Mirrors) stress that preliminary measurements must evaluate wall deflection, backing substrate flatness, and hardware cutouts for electrical outlets or fixtures. According to NGA technical publications, standard one-quarter-inch (6 mm) mirror stock is recommended for full-height wall panels to limit optical image distortion across broad surface areas, while three-sixteenths-inch stock is commonly selected for smaller framed residential vanities.

In addition to standard wall panels, the expanded facility handles specialty custom furniture pieces, including mirrored pedestals and decorative display enclosures. During fabrication, technicians apply protective edge sealants to mitigate silver-backing corrosion?commonly referred to in the glass industry as "black edge"?caused by moisture and chemical exposure in humid master bathrooms and commercial spa environments. Field installation crews utilize aluminum J-channels with 3 mm neoprene setting blocks, mechanical mounting clips, and neutral-cure mirror adhesives compatible with silver backing paint to secure completed units.

During pre-installation site visits, field specialists evaluate substrate conditions using digital leveling instruments and laser measures. Identifying wall stud irregularities or bow angles prior to mounting allows technicians to position setting shims and mechanical anchors, establishing a plumb mounting plane that protects the glass substrate from point-load mechanical stress. On-site assessments also assist commercial buyers in selecting edge finishes?such as flat-polished or beveled edges?that conform to building layout specifications.

Founded in 1956, Alamo Glass provides custom mirror fabrication, precise cutting, and professional installation services for residential and commercial clients across Central Texas. Operating from its long-standing facility and showroom on North Lamar Boulevard, the locally owned business delivers technical consultations, site measurements, and custom mirrors in Austin, TX for builders, interior designers, and property owners. For more information, visit alamoaustin.com.

###

For more information about Alamo Glass, contact the company here:Alamo GlassAlamo Glass(512) 452-5731info@alamoaustin.comAustin, TX

Alamo Glass

Website: https://www.alamoaustin.com/

Email: info@alamoaustin.com

Phone: (512) 452-5731